



UniTV EX273

- 6000nit brightness! Fine play under direct sunlight
- 3840Hz refresh rate, silky smooth image quality
- IP65 waterproof, be ready for harsh environment
- Wall mount, ground mount, pole mount options
- Smart phone APP remote control



Technical Specifications

Pixel Pitch	4.81mm
Pixel Configuration	SMD1921
Brightness	6000nit
LED Module Size WxH	250x250mm
LED TV Size (WxH, mm)	6000x3500mm
LED TV Size (WxH, ft)	19.69x11.48ft
LED TV Resolution	1248x728pix
Viewing Angle (Horizontal/Vertical)	140°/140°
Recommended Viewing Distance	5-15m
Cabinet Material	Aluminum
Net Weight	1050kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	14bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 15750W, Typical 4725W
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Maintenance	Front / Rear serviceable
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair