



UniTour EX15

- Unique outdoor moving digital signage, to be No.1!
- 20min installation, catch every moment to maximize AD reach
- Adjustable ground clearance, reach high to catch eyes
- Smart phone control, one-click projection for Fans interaction
- Compatible with various LED panels



Technical Specifications

Pixel Pitch	2.976mm
Pixel Configuration	SMD1415
Brightness	5000nit
LED Cabinet Size WxH	500x500mm
Display Size WxH	2500x1500mm
Display Resolution	840x504
Ground Clearance	1-2.8m
Weight (incl. trailer box)	332.5kg
Recommended Viewing Distance	3-10m
Cabinet Material	Die-casting aluminum
Lifting mode	Electric rod remote control
Protection grade	IP65
Color Temperature	3000-9500K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 2438W, Typical 731W
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Lifting Speed	4mm/s
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Maintenance	Rear Service
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair