




UniClear P5.2

- Max 5500nit brightness adjustable, 24/7 always bright
- LED strip 3.5mm thick, like putting a shutter on the window
- Ultra thin frame, the cross between the panels is barely visible
- Customized LED panel size to fit the window size
- 7.2kg/sqm ultra light weight, fast install hanging from the roof
- Curved shape LED panel available



Technical Specifications

Pixel Pitch	Horizontal 5.2mm, Vertical 10.4mm
Pixel Configuration	SMD1921
Brightness	5500nit
Transparency	75%
Typical LED Cabinet Size WxHxD	1000x500x3.5mm (exclude power box)
Typical Cabinet Resolution	192x48
Horizontal Viewing Angle	+/-80°
Vertical Viewing Angle	+/-80°
Recommended Viewing Distance	5-15m
Cabinet Material	Aluminum profile
Cabinet Weight	7.2kg/sqm
Protection grade	IP41
Color Temperature	5500-9300K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920Hz
Power Consumption	Max 700W/sqm, Typical 210W/sqm
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Maintenance	Rear service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair