



UniPoster IN1.8

- 1000nit brightness, stay bright in ambient lighting
- 3840Hz refresh, silky smooth image quality
- 40kg, easy to move, both for permanent use and event
- Complete ports for USB, HDMI, audio device connection
- 5pcs or more cascade to make a big screen



Technical Specifications

Pixel Pitch	1.86mm
Pixel Configuration	SMD1515
Brightness	1000nit
LED Module Size WxH	320x160mm
Typical LED Cabinet Size WxHxD	640x1920x50mm
Typical Cabinet Resolution	344x1032
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	2-6m
Cabinet Material	Aluminum profile
Weight	40kg
Protection grade	IP41
Color Temperature	2000-9500K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 740W, Typical 222W
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Maintenance	Rear service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair