



UniPoster EX3.3

- 5500nit brightness, 24/7 working behind window or in sunlight
- 3840Hz refresh, silky smooth image quality
- IP65 waterproof, get ready for harsh environment
- Smart phone APP control, real-time content update
- Dual sided available, display size customizable



Technical Specifications

Pixel Pitch	3.33mm
Pixel Configuration	SMD1921
Brightness	5500nit
LED Module Size WxH	320x160mm
Typical LED Cabinet Size WxHxD	1280x1760x100mm
Typical Cabinet Resolution	384x528
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	3-10m
Cabinet Material	Aluminum
Weight	100kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	14bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920 / 3840Hz
Power Consumption	Max 1690W, Typical 507W
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Maintenance	Rear service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair