



UniBanner MINI1.2

- 300x60mm panel size, to fit price tag area
- COB/GOB surface, IP65 waterproof, easy to clean
- Smart phone APP control, real-time content update
- 10000:1 highest color contrast, bring best colors to customers
- Horizontal cascade up to 4.8m length



Technical Specifications

| | |
|----------------------------------|---|
| Pixel Pitch | 1.25mm |
| Pixel Configuration | COB 1R1G1B |
| Brightness | 500nit |
| Module Size | 300x60mm |
| LED Cabinet Size WxHxD | 300x60x23.5mm |
| Cabinet Resolution | 240x45 |
| Horizontal Viewing Angle | +/-85° |
| Vertical Viewing Angle | +/-85° |
| Recommended Viewing Distance | 1.2-4m |
| Cabinet Material | Aluminum profile |
| Cabinet Weight | 0.35kg |
| Protection grade | IP65 |
| Color Temperature | 3200-9300K Adjustable |
| Grey Scale | 16bit |
| Contrast Ratio | 10000:1 |
| Video Frame Rate | 50/60Hz |
| Refresh Rate | 3840Hz |
| Power Consumption | Max 15W, Typical 5W |
| Storage Temperature / Humidity | -30~+60°C, 10~95%RH |
| Operating Temperature / Humidity | -20~+50°C, 10~90%RH |
| Maintenance | Front service |
| Input Voltage | 100-240V AC |
| Input Signal | DVI/HDMI/VGA/SDI/DP/AV/S-Video |
| Brightness Control | Manual / Automatic |
| LED Lifetime | >100,000 Hours |
| Service | Design, Configuration, Installation, Local repair |