



UniBanner MINI1.8

- 300x60mm panel size, to fit price tag area
- COB/GOB surface, IP65 waterproof, easy to clean
- Smart phone APP control, real-time content update
- 10000:1 highest color contrast, bring best colors to customers
- Horizontal cascade up to 7.2m length



Technical Specifications

Pixel Pitch	1.88mm
Pixel Configuration	SMD1515 +GOB
Brightness	500nit
Module Size	300x60mm
LED Cabinet Size WxHxD	300x60x23.5mm
Cabinet Resolution	160x32
Horizontal Viewing Angle	+/-85°
Vertical Viewing Angle	+/-85°
Recommended Viewing Distance	1.8-6m
Cabinet Material	Aluminum profile
Cabinet Weight	0.35kg
Protection grade	IP65
Color Temperature	3200-9300K Adjustable
Grey Scale	16bit
Contrast Ratio	10000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 15W, Typical 5W
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-20~+50°C, 10~90%RH
Maintenance	Front service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair