



UniBillboard P5

- 6500nit brightness, 24/7 non-stop working day and night
- Energy saving circuit design, saves 30% electricity every year
- Surface temperature no higher than 50°C, 10 years lifespan
- 27kg LED cabinet, save structure and labor costs
- IP65 waterproof, get ready for harsh environment

Technical Specifications

Pixel Pitch	5mm
Pixel Configuration	SMD2727
Brightness	6500nit
LED Module Size WxH	320x160mm
LED Cabinet Size WxHxD	960x960x106mm (1280x960mm option)
LED Cabinet Resolution	192x192
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	5-15m
Cabinet Material	Die-casting aluminum
Cabinet Weight	27kg
Protection grade	IP65
Color Temperature	3200-12000K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920 / 3840Hz
Power Consumption	Max 500W, Typical 166W
Storage Temperature / Humidity	-30~+70°C, 10~95%RH
Operating Temperature / Humidity	-30~+60°C, 10~95%RH
Maintenance	Rear Service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair

