



UniDisplay EX6.6 Pro

- 6000nit brightness! 24/7 non-stop working day and night
- IP65 waterproof, get ready for harsh environment
- Cable inner passing, keep the display protective
- Direct wall mount install, no need for back space or structures
- Cabinet size customizable



Technical Specifications

Pixel Pitch	6.67mm
Pixel Configuration	SMD2727
Brightness	6000nit
LED Module Size WxH	320x320mm
LED Cabinet Size WxHxD	960x960x120mm
LED Cabinet Resolution	144x144
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	6-20m
Cabinet Material	Steel or aluminum
Cabinet Weight	42kg or 37kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	14bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920 / 3840Hz
Power Consumption	Max 690W, Typical 210W
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-30~+60 °C, 10~95%RH
Maintenance	Front Service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair