



# UniSign EX3.3

- 6000nit brightness, 24/7 non-stop working day and light
- IP65 waterproof, get ready for harsh environment
- Direct wall mount installation, no need extra structures
- Smart phone APP control, cluster control
- Customizable display size, dual sided display available



## Technical Specifications

Pixel Pitch	3.3mm
Pixel Configuration	SMD1921
Brightness	6000nit
LED Module Size WxH	320x160mm
Typical LED Cabinet Size WxHxD	1600x960x150mm (customizable)
Typical Cabinet Resolution	480x288
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	3-10m
Cabinet Material	Aluminum
Cabinet Weight	72kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	14bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920Hz
Power Consumption	Max 1152W, Typical 346W
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-30~+60°C, 10~95%RH
Maintenance	Front open service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair