



UniSign EX8

- 6000nit brightness, 24/7 non-stop working day and light
- IP65 waterproof, get ready for harsh environment
- Direct wall mount installation, no need extra structures
- Smart phone APP control, cluster control
- Customizable display size, dual sided display available



Technical Specifications

Pixel Pitch	8mm
Pixel Configuration	SMD3535
Brightness	6000nit
LED Module Size WxH	320x160mm
Typical LED Cabinet Size WxHxD	1600x960x150mm (customizable)
Typical Cabinet Resolution	200x120
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	8-25m
Cabinet Material	Aluminum
Cabinet Weight	72kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	14bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920Hz
Power Consumption	Max 1152W, Typical 346W
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-30~+60°C, 10~95%RH
Maintenance	Front open service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair