











## **UniPerimeter EX6**

- 6500nit brightness, always bright in sunlight
- 3840Hz refresh rate, silky smooth image under live camera
- Top PU pad, rubber mask to protect player from getting hurt
- Rotatable stand, two sides wheels, easy to move
- Customizable cabinet size
- 10 years lifespan





## **Technical Specifications**

| Pixel Pitch                      | 6.67mm  |
|----------------------------------|---|
| Pixel Configuration              | SMD3535   |
| Brightness                       | 6500nit   |
| LED Module Size WxH              | 320x320mm   |
| Typical LED Cabinet Size WxHxD   | 1280x960x150mm (customizable)                     |
| Typical Cabinet Resolution       | 192x144   |
| Horizontal Viewing Angle         | +/-70°  |
| Vertical Viewing Angle           | +/-70°  |
| Recommended Viewing Distance     | 6-20m   |
| Cabinet Material                 | Aluminum  |
| Cabinet Weight                   | 50kg  |
| Protection grade                 | IP65  |
| Color Temperature                | 2000-9500K Adjustable                             |
| Grey Scale                       | 16bit   |
| Contrast Ratio                   | 3000:1  |
| Video Frame Rate                 | 50/60Hz   |
| Refresh Rate                     | 3840Hz  |
| Power Consumption                | Max 920W, Typical 276W                            |
| Storage Temperature / Humidity   | -30~+70℃, 10~95%RH                                |
| Operating Temperature / Humidity | -30~+60℃, 10~95%RH                                |
| Maintenance                      | Front or rear service                             |
| Input Voltage                    | 100-240V AC                                       |
| Input Signal                     | DVI/HDMI/VGA/SDI/DP/AV/S-Video                    |
| Brightness Control               | Manual / Automatic                                |
| LED Lifetime                     | >100,000 Hours                                    |
| Service                          | Design, Configuration, Installation, Local repair |