



UniPerimeter EX8

- 6500nit brightness, always bright in sunlight
- 3840Hz refresh rate, silky smooth image under live camera
- Top PU pad, rubber mask to protect player from getting hurt
- Rotatable stand, two sides wheels, easy to move
- Customizable cabinet size
- 10 years lifespan



Technical Specifications

Pixel Pitch	8mm
Pixel Configuration	SMD3535
Brightness	6500nit
LED Module Size WxH	320x320mm
Typical LED Cabinet Size WxHxD	1280x960x150mm (customizable)
Typical Cabinet Resolution	160x120
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	8-25m
Cabinet Material	Aluminum
Cabinet Weight	50kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	16bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 920W, Typical 276W
Storage Temperature / Humidity	-30~+70°C, 10~95%RH
Operating Temperature / Humidity	-30~+60°C, 10~95%RH
Maintenance	Front or rear service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair