



UniDisplay IN3

- 1000nit brightness, always bright in ambient lighting
- 1.2~4mm pixel pitch for option
- 74mm thickness only, make a digital masterpiece on the wall
- Direct wall mount install, no need for structures
- 5000:1 high contrast ratio, play perfect colors to customers



Technical Specifications

Pixel Pitch	3.33mm
Pixel Configuration	SMD2020
Brightness	1000nit
LED Module Size WxH	320x160mm
LED Cabinet Size WxHxD	640x480x74mm
Cabinet Resolution	192x144
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	3-10m
Cabinet Material	Die-casting aluminum
Cabinet Weight	6.8kg
Protection grade	IP45
Color Temperature	3200-9300K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 170W, Typical 51W
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-20~+50°C, 10~90%RH
Maintenance	Front service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair