



# UniDisplay IN4

- 1000nit brightness, always bright in ambient lighting
- 1.2~4mm pixel pitch for option
- 74mm thickness only, make a digital masterpiece on the wall
- Direct wall mount install, no need for structures
- 5000:1 high contrast ratio, play perfect colors to customers



## Technical Specifications

Pixel Pitch	4mm
Pixel Configuration	SMD2020
Brightness	1000nit
LED Module Size WxH	320x160mm
LED Cabinet Size WxHxD	640x480x74mm
Cabinet Resolution	160x120
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	4-12m
Cabinet Material	Die-casting aluminum
Cabinet Weight	6.8kg
Protection grade	IP45
Color Temperature	3200-9300K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 170W, Typical 51W
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-20~+50°C, 10~90%RH
Maintenance	Front service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair