



UniWall P1.8

- 1000nit brightness, always bright in ambient lighting
- 8000:1 highest contrast ratio, show truest and richest colors
- 39mm thickness only, make a digital masterpiece on the wall
- Direct wall mount install, no need for structures
- Hard-wired design with only one main power cable out



Technical Specifications

Pixel Pitch	1.88mm
Pixel Configuration	SMD1515
Brightness	1000nit
LED Module Size WxH	150x168.75mm
LED Cabinet Size WxHxD	600x337.5x39mm
Cabinet Resolution	320x180
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	1.8-6m
Cabinet Material	Die-casting aluminum
Cabinet Weight	6kg
Protection grade	IP45
Color Temperature	3000-12000K Adjustable
Grey Scale	16bit
Contrast Ratio	8000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 600W/sqm, Typical 180W/sqm
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Maintenance	Front service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair