



## UniWall P2.5

- 1000nit brightness, always bright in ambient lighting
- 8000:1 highest contrast ratio, show truest and richest colors
- 39mm thickness only, make a digital masterpiece on the wall
- Direct wall mount install, no need for structures
- Hard-wired design with only one main power cable out



### Technical Specifications

Pixel Pitch	2.5mm
Pixel Configuration	SMD1515
Brightness	1000nit
LED Module Size WxH	150x168.75mm
LED Cabinet Size WxHxD	600x337.5x39mm
Cabinet Resolution	240x135
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	2.5-8m
Cabinet Material	Die-casting aluminum
Cabinet Weight	6kg
Protection grade	IP45
Color Temperature	3000-12000K Adjustable
Grey Scale	16bit
Contrast Ratio	8000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 600W/sqm, Typical 180W/sqm
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-20~+50°C, 10~90%RH
Maintenance	Front service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair