



UniCurtain EX5.2

- Max 5500nit brightness, be ready for daylight use
- 3840Hz refresh rate, silky smooth image under camera
- 3.75kg only per panel, save freight, labor and structure costs
- 5000:1 high contrast ratio, bring the best viewing experience
- Curvable and right-angled LED cabinet available



Technical Specifications

| | |
|----------------------------------|---|
| Pixel Pitch | Horizontal 5.2mm, Vertical 10.4mm |
| Pixel Configuration | SMD1921 |
| Brightness | 4500nit |
| Transparency | 58% |
| Typical LED Cabinet Size WxHxD | 1000x500x76mm |
| Typical Cabinet Resolution | 192x48 |
| Horizontal Viewing Angle | +/-80° |
| Vertical Viewing Angle | +/-80° |
| Recommended Viewing Distance | 5-15m |
| Cabinet Material | Die-casting aluminum |
| Cabinet Weight | 7.5kg |
| Protection grade | IP65 |
| Color Temperature | 5500-9300K Adjustable |
| Grey Scale | 16bit |
| Contrast Ratio | 5000:1 |
| Video Frame Rate | 50/60Hz |
| Refresh Rate | 3840Hz |
| Power Consumption | Max 800W/sqm, Typical 260W/sqm |
| Storage Temperature / Humidity | -30~+60 °C, 10~95%RH |
| Operating Temperature / Humidity | -20~+50 °C, 10~90%RH |
| Maintenance | Front or rear service |
| Input Voltage | 100-240V AC |
| Input Signal | DVI/HDMI/VGA/SDI/DP/AV/S-Video |
| Brightness Control | Manual / Automatic |
| LED Lifetime | >100,000 Hours |
| Service | Design, Configuration, Installation, Local repair |