



# UniModule IN1.2

- 1000nit brightness, always bright in ambient lighting
- 1.2~10mm pixel pitch for option
- Magnetic beads, directly mount to cabinet or wall structure
- 5000:1 high contrast ratio, bring perfect color quality
- 5 years lifespan

## Technical Specifications

|                                  |   |
|----------------------------------|---|
| Pixel Pitch                      | 1.25mm  |
| Pixel Configuration              | SMD1010   |
| Pixel Density                    | 640,000pix/sqm                                    |
| Brightness                       | 1000nit   |
| LED Module Size WxHxD            | 320x160x17mm                                      |
| LED Module Resolution            | 256x128   |
| Driving Type                     | 1/64  |
| Weight                           | 580g  |
| Horizontal Viewing Angle         | +/-70°  |
| Vertical Viewing Angle           | +/-70°  |
| Viewing Distance                 | 1.2-4m  |
| Protection grade                 | IP40  |
| Color Temperature                | 3000-9500K Adjustable                             |
| Grey Scale                       | 16bit   |
| Contrast Ratio                   | 5000:1  |
| Video Frame Rate                 | 50/60Hz   |
| Refresh Rate                     | 3840Hz  |
| Storage Temperature / Humidity   | -30~+60°C, 10~95%RH                               |
| Operating Temperature / Humidity | -20~+50°C, 10~90%RH                               |
| Maintenance                      | Front service                                     |
| Input Voltage                    | 100-240V AC                                       |
| Input Signal                     | DVI/HDMI/VGA/SDI/DP/AV/S-Video                    |
| Brightness Control               | Manual / Automatic                                |
| LED Lifetime                     | >100,000 Hours                                    |
| Service                          | Design, Configuration, Installation, Local repair |

