





UniModule IN3

- 1000nit brightness, always bright in ambient lighting
- 1.2~10mm pixel pitch for option
- Magnetic beads, directly mount to cabinet or wall structure
- 5000:1 high contrast ratio, bring perfect color quality
- 5 years lifespan



Technical Specifications

Pixel Pitch	3.33mm
Pixel Configuration	SMD2020
Pixel Density	90,000pix/sqm
Brightness	1000nit
LED Module Size WxHxD	320x160x17mm
LED Module Resolution	96x48
Driving Type	1/24
Weight	380g
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Viewing Distance	3.3-10m
Protection grade	IP40
Color Temperature	3000-9500K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	1920Hz
Storage Temperature / Humidity	-30~+60°C, 10~95%RH
Operating Temperature / Humidity	-20~+50°C, 10~90%RH
Maintenance	Front service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair