



UniT-box ED1

- 1.6~4.3m adjustable ground clearance
- electric rod to lift, remote control
- 20 minutes to install, maximize advertising reach
- IP65 waterproof, get ready for harsh environment
- Compatible with various LED panels



Technical Specifications

Dimension WxHxD (mm)	800x1600x900
Dimension WxHxD (inch)	31.5x62.99x35.43
Ground Clearance (mm)	1600~4300
Ground Clearance (ft)	5.25~14.1
LED Display Size	115" / 158"
LED Display Resolution	480P / 640P
Fixing Position	Every 300mm (Every 11.81inch)
Material	Steel
Weight	220kg
Lifting Type	Electric rod, remote control
Lifting Speed	4mm/s (0.16in/s)
Protection Grade	IP65
Hanging Beam Length (m)	2.5 / 3.5
Hanging Beam Length (ft)	8.2 / 11.48
Extendable Feet Quantity	6
Extendable Feet Distance	0~600mm (0~1.97ft), manual
Power Supply	100-240V AC
Storage Temp / Humidity	-30~+70°C, 10~95%RH
Operating Temp / Humidity	-30~+60°C, 10~95%RH
Load Capacity	500kg
Wheel Quantity	4
Certification	CE, UL, ETL
Lifetime	5 years
Protection Device	Over temperature protection sensor
Maintenance	Routine clean service
Service	Design, Configuration, Installation, Local repair