



UniPerimeter IN4

- 1000nit brightness, always bright in ambient lighting
- 3840Hz refresh rate, silky smooth image under live camera
- Top PU pad, protect players from getting hurt
- Rotatable stand, side wheels options, easy to move
- Customizable cabinet size



Technical Specifications

Pixel Pitch	4mm
Pixel Configuration	SMD2121
Brightness	1000nit
LED Module Size WxH	320x160mm
Typical LED Cabinet Size WxHxD	960x960x100mm
Typical Cabinet Resolution	240x240
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	4-12m
Cabinet Material	Aluminum
Cabinet Weight	45kg
Protection grade	IP45
Color Temperature	2000-9500K Adjustable
Grey Scale	16bit
Contrast Ratio	5000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 690W, Typical 195W
Storage Temperature / Humidity	-30~+60 °C, 10~95%RH
Operating Temperature / Humidity	-20~+50 °C, 10~90%RH
Maintenance	Rear Service
Input Voltage	100-240V AC
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Manual / Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair